



Data sheet DLoG X 7

DLoG antenna
Mechanically stable.
Optimum transmission
characteristics.
Reliable, fast data transfer.

Protection class
IP 54 / IP 65 / IP 66 / IP 67
for the entire system.

Mounting
Over 70 mounting solution
alternatives.
Stationary and mobile.
Also for non-suspension
vehicles.



Thermal concept
Freezer capable.
Robust against fast changing
temperatures.

DLoG touch screen
Simple and precise operation.
High breakage resistance.

Mechanical design
Optimal mechanical protection.
Secure against vibrations, impact
and environmental conditions.
Tougher testing standards than
the US MIL-Std.

Variations

We offer a large selection of design variations and accessories, such as:

4 or 17 Front keys



Landscape



External keyboard and scanner



DLoG X 7 is a compact, industrial capable Windows® CE terminal. WLAN/GSM connection, a 7" color TFT with touch screen, high IP protection as well as shock and vibration resistance make the DLoG X 7 the ideal terminal for modern logistics and industrial applications.

Used in outside or freezer areas, it bears up in extreme temperatures and is reliable and safe.



Specifications DLoG X 7

Housing		Coated Aluminium Fanless design
Dimension		9.0" x 6.2" x 3.3" / 229 x 158 x 85 mm
Weight		2.5 kg
Display (internal)		Color-TFT, 7", WQVGA, 480 x 234, 500 cd/m ² Portrait and landscape use possible
Touch screen		DLoG specific resistive touch screen
System properties		
CPU		Marvell® PXA270 to 520 MHz
Memory		64 MB SDRAM / 64 MB Flash or 128 MB SDRAM / 128 MB Flash
Graphics		Integrated LCD-Controller
Software		
Operating system		MS® Windows® CE 5.0, CE 6.0 on request
Emulations		VT100, VT220, IBM 5250, TN 3270 Citrix ICA Client® RDP Client
Interfaces		
Serial		2 RS232 interfaces, alternatively 1 x RS232 and 1 x RS422/485 Optional feature: COM 1, 5 V or 12 V
USB		2 USB 2.0 (low and full speed) interfaces, 1 host and 1 client or 2 host
Keyboard / Mouse		Externally via USB port
Ports		
PC-Card (16-bit)		1 x type I / type II
CF		1 x type I
Network		
WLAN		WLAN 802.11b/g
Extension card		
USB		4 USB ports
Power supply		
AC		110/230 VAC, 30 W, 50 to 60 Hz
DC		12/24 VDC or 24/48 VDC, 36 W, galvanically isolated Voltage sags up to 5 VDC can be handled for up to 20 sec.
Environmental specifications		
Protection class		IP 54 / IP 65 / IP 66 / IP 67
Certificates		CE/FCC Class A
Operating temperature		-32° to +122 °F / 0° to +50 °C -22° to +122 °F / -30° to +50 °C(option)
Storage temperature		-31° to +149 °F / -35° to +65 °C
Relative humidity		10% to 90% at 104 °F / 40 °C, non- condensing
Vibration / Shock		Class 5M3 according to EN 60721-3-5 and US Highway Truck as MIL-STD 810F

Highlights

Brightness control: Via integrated front keys / automatically

DLoG Config Tool: Diagnostics and individual configuration of the Client

Automatic shut down: Initiated by the ignition signal (automatically) or by the On/Off switch (manually) the operating system is properly shut down and the device is switched off.

Environment controller : Statistics, configuration and monitoring functions (temperature, ignition, backlight, etc.)

Shock and vibration tests to stringent DIN and US Standards: DLoG terminals are suitable for use in locations where heavy vibrations and impacts occur, for example on non-suspension vehicles or machines with substantial imbalances.

Information in this document is subject to change without prior notice. The software and hardware designations used in this text are in most cases also registered trademarks and are thus subject to law.

© by DLoG GmbH 2008

DLoG GmbH
Werner-von-Siemens-Str. 13
D-82140 Olching
Phone: +49 81 42 / 28 60-0
Fax: +49 81 42 / 28 60-10
E-Mail: info@dlog.com
Internet: www.dlog.com